


## TYPE 2 GENERAL PURPOSE CAVITY WALL TIE MPT200/ MPT225/ MPT250



Cavity (mm)	Reference	Tie length (mm)
75	MPT200	200
100	MPT225	225
125	MPT250	250

1.4301 Austenitic Stainless Steel to BS EN 10088-3 : 2005.

Supplied in boxes of 250

Insulation clip SSCD is also available



### Standards and Conformity

BS EN 845-1 Specification For Ancillary Components in Masonry - Part 1 :Ties, tension straps, hangers and brackets.  
Declared Loads over a 100mm cavity

Test	Declared value (N)
Tension	2163
Compression	1389

BS 5628-1 Code of practice for the use of masonry - Part 1: Structural use of unreinforced masonry.  
Type 2 tie

Approved Document E: Resistance to the passage of sound  
Tie type B. Dynamic stiffness < 113MN/m<sup>3</sup> at tie density of 2.5 ties/m<sup>2</sup> at a 75mm working cavity.

### Features

Safety ends reduce the risk of injury during handling and installation.  
Light weight making installation quick, easy and economical.

### Installation

Code of practice BS 5628-1 states that walls that have leaves 90mm or thicker should include wall ties at not less than 2.5 ties per m<sup>2</sup>. Stagger wall ties in alternate courses at 900mm horizontal and 450mm vertical spacings. Wall ties adjacent to openings in masonry panels, vertical movement joint locations or non returned edges should be positioned at a maximum 300mm vertical spacing and no more than 225mm away from the opening. The MPT tie must be bedded into fresh mortar at the time of the wall construction ensuring nominal 62.5mm embedment in each leaf. The cavity spanning section of the tie is to be kept free of mortar.

### Accessories

The MPT Type 2 Wall Tie can be used in conjunction with the Expamet Building Products SSCD insulation retaining clip.



## TYPE 2 GENERAL PURPOSE CAVITY WALL TIE MPT200/ MPT225/ MPT250

### Contact information

Technical:  
Telephone 01429 866655  
Email [technical@expamet.net](mailto:technical@expamet.net)  
Fax 01429 866622

Sales:  
Telephone 01429 866611  
E-mail [sales@expamet.net](mailto:sales@expamet.net)  
Fax 01429 866622

### Expamet Health and Safety

#### 1. IDENTIFICATION

Expamet Building Products Limited  
Greatham Street  
Longhill Industrial Estate (North)  
Hartlepool TS25 1PR  
United Kingdom  
Telephone 01429 866688  
Fax 01429 866633

#### 2. COMPOSITION

Stainless steel 1.4301 to BS EN 10088-3: 2005

#### 3. HAZARDS IDENTIFICATION

Possible cuts from steel edges.  
Toxic and irritant fumes from high temperatures.

#### 4. FIRST AID MEASURES

Skin and eye contact: treat cuts from steel edges as required.  
Ingestion: not applicable.  
Inhalation: remove from source of fumes and dust.

#### 5. FIRE FIGHTING MEASURES

Non-flammable material.

#### 6. ACCIDENTAL RELEASE MEASURES

Not applicable.

#### 7. HANDLING AND STORAGE

Use suitable PPE when handling all products. Assess manual handling risks before lifting. All products should be stacked on firm level ground in dry conditions.

#### 8. EXPOSURE CONTROLS

Wear personal protection such as gloves and safety goggles when handling products.  
Some products may have a film of soluble cutting fluid after manufacture; therefore carry out personal hygiene, including proper washing of hands, after contact.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Construction products are supplied in various lengths, widths and gauges. Metallic grey appearance.

#### 10. STABILITY AND REACTIVITY

All products are stable under normal conditions but if subjected to high temperatures, fumes are produced.

#### 11. TOXICOLOGICAL INFORMATION

High temperatures can produce fumes.

#### 12. ECOLOGICAL INFORMATION

No known hazard.

#### 13. DISPOSAL CONSIDERATIONS

Recycle or dispose of in accordance with Waste Management Licensing Regulations.

#### 14. TRANSPORT INFORMATION

Not classified as hazardous for transport.

#### 15. REGULATORY INFORMATION

Construction products are articles therefore not subject to CHIP3.

#### 16. OTHER INFORMATION

All products must be installed in accordance with Expamet Building Product's published instructions.  
This Health and Safety Data Sheet is not a product specification guide.

Any arrangement of Expamet Construction products shown in this datasheet is indicative only. Actual fixing installations must comply with current Health and Safety requirements.

Expamet operates a continuous development programme and we reserve the right to amend specification with prior notification

Expamet Building Products Limited, Greatham Street, Longhill Industrial Estate (North) Hartlepool TS25 1PR  
Telephone 01429 866611 Fax 01429 866622 Email [info@expamet.net](mailto:info@expamet.net)

